



PLUG COMPONENT			PLUG STRIP DIMENSION			END STRIP DIMENSION				TERMINAL COMPONENT	
COLOR	DESCRIPTION	Q'ty	R.I.J	R.O.J	COLOR	SJT 16AWGx3C	R.O.J	R.I.J	COLOR	DESCRIPTION	TYPE
40P BLACK	PVC Compound	1	6 ⁺¹ ₋₀	19 ± 1	BLACK(L)	105°C Shielded Black Length 1000±20	15 ⁺³ ₋₀		BLACK(L)		
Gray color	Assembly Body 111-003-001	1	6 ⁺¹ ₋₀	19 ± 1	WHITE(N)		15 ⁺³ ₋₀		WHITE(N)		
			6 ⁺¹ ₋₀	19 ± 1	GREEN(E)		15 ⁺³ ₋₀		GREEN(E)		



Plug type




Material:


- SJT 3 x 16AWG(1.31mm²) VW-1 Shielded, 105°C 300V
- Jacket Color: Black
- E - Green; L - Black; N - White

Electrical:

- 100% Open & Short Testing
- Insulation Resistance: 100MΩ (min.)
- Voltage: 500V DC / 1 minute




Hank Dimension



Wire Cross section

Unit: mm



Scale	Free				Date	Name	Title
TOLERANCE					Drawn	10.10.15	Wilson
X.	±X				Approved	10.10.15	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet

Title		Power cord - SJT	
		105°C 16AWG Open End, Shielded 1 Meter	
ASSMANN WSW-No.		AK500/16-OE-7-1	
Drawing-No.		rev00	
Replace		Sheet 1/1	

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@assmann.us