

DESCRIPTION OF REVISIONS		BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS		BY	CHKD	DATE	
△					△						
△					△						
<b>APPLICABLE STANDARD</b>											
RATING	OPERATING TEMPERATURE RANGE	- 3 5 °C TO 8 5 °C(NOTE1)			STORAGE TEMPERATURE RANGE	- 1 0 °C TO 6 0 °C					
	VOLTAGE	5 0 V A C			APPLICABLE CONNECTOR	DF23A/C-*DP-0.5V					
	CURRENT	0. 3 A									
<b>SPECIFICATIONS</b>											
ITEM		TEST METHOD			REQUIREMENTS			QT	AT		
<b>CONSTRUCTION</b>											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			x	x		
MARKING		CONFIRMED VISUALLY.						x	x		
<b>ELECTRICAL CHARACTERISTICS</b>											
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			60 mΩ MAX.			x	-		
INSULATION RESISTANCE		100 V DC.			500 MΩ MIN.			x	-		
VOLTAGE PROOF		150 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			x	-		
<b>MECHANICAL CHARACTERISTICS</b>											
MECHANICAL OPERATION		50 TIMES INSERTIONS AND EXTRactions.			① CONTACT RESISTANCE: 60 mΩ MAX ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	-		
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm AT 2 h FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	-		
SHOCK		490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	-		
<b>ENVIRONMENTAL CHARACTERISTICS</b>											
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS			x	-		
RAPID CHANGE OF TEMPERATURE		TEMPERATURE: -55→ 5 TO 35→85→ 5 TO 35 °C TIME: 30→10 TO 15→30→10 TO 15 min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 60 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	-		
CORROSION SALT MIST		EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			x	-		
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEIDA-39)			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			x	-		
<b>REMARKS</b>											
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED			
Unless otherwise specified, refer to MIL-STD-1344.				J. Goi '01.3.14	J. Goi '01.3.14	S. Tashiro '01.3.16	K. Katayama '01.3.16				
Note QT: Qualification Test AT: Assurance Test x: Applicable Test											
<b>HRS</b> HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO. DF23C-*DS-0.5V(51)				
CODE NO.(OLD) CL			DRAWING NO E L C 4 - 1 6 3 5 4 3 - 0 1			CODE NO. C L 6 8 8 -			1	1	

Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

TO