

	1	2	3	4	5	6	7																																																									
A																																																																
B	<p>Specifications:</p> <p>Material: Poly Carbonate(PC) UL94V-2 Housing: High strength copper alloy Contact blade: High strength copper alloy 100 micron Nickel underplated Plating type: 8% Phosphor Bronze Plating thickness: 6u" gold plated Operating temperature: -40°C to +125°C</p>																																																															
C	<p>Electrical:</p> <p>Current rating: 250V AC max. at 2A Dielectric: 500V AC Insulation resistance: 500MQ Termination resistance: 35MQ max after environmental tests Tensile strength: 20 LBS (89N) min. Durability: 500 mating cycles</p> <p>Complies with FCC68/F</p>																																																															
D																																																																
E																																																																
F																																																																
G	<p>RoHS compliant Unit: mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free TOLERANCE</th> <th>Free TOL</th> <th>Id.</th> <th>Date</th> <th>Name</th> <th>Customer-F-No.</th> <th>Drawing-No.</th> </tr> </thead> <tbody> <tr> <td>X.X</td> <td>±0.20</td> <td></td> <td></td> <td>26.05.2014</td> <td>Ray</td> <td></td> <td>ASS 6448 CO</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td>03.05.2016</td> <td>Amy</td> <td></td> <td>A-MO 4/4-SF</td> </tr> <tr> <td>X.XXX</td> <td>±0.05</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>±2°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free TOLERANCE	Free TOL	Id.	Date	Name	Customer-F-No.	Drawing-No.	X.X	±0.20			26.05.2014	Ray		ASS 6448 CO	X.XX	±0.10			03.05.2016	Amy		A-MO 4/4-SF	X.XXX	±0.05							DIM	TOL							Angle	±2°							Angle								
Scale	Free TOLERANCE	Free TOL	Id.	Date	Name	Customer-F-No.	Drawing-No.																																																									
X.X	±0.20			26.05.2014	Ray		ASS 6448 CO																																																									
X.XX	±0.10			03.05.2016	Amy		A-MO 4/4-SF																																																									
X.XXX	±0.05																																																															
DIM	TOL																																																															
Angle	±2°																																																															
Angle																																																																
H	<table border="1"> <thead> <tr> <th>Scale</th> <th>Free TOLERANCE</th> <th>Free TOL</th> <th>Id.</th> <th>Date</th> <th>Name</th> <th>Customer-F-No.</th> <th>Drawing-No.</th> </tr> </thead> <tbody> <tr> <td>X.X</td> <td>±0.20</td> <td></td> <td></td> <td>26.05.2014</td> <td>Ray</td> <td></td> <td>ASS 6448 CO</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td>03.05.2016</td> <td>Amy</td> <td></td> <td>A-MO 4/4-SF</td> </tr> <tr> <td>X.XXX</td> <td>±0.05</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>±2°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free TOLERANCE	Free TOL	Id.	Date	Name	Customer-F-No.	Drawing-No.	X.X	±0.20			26.05.2014	Ray		ASS 6448 CO	X.XX	±0.10			03.05.2016	Amy		A-MO 4/4-SF	X.XXX	±0.05							DIM	TOL							Angle	±2°							Angle								
Scale	Free TOLERANCE	Free TOL	Id.	Date	Name	Customer-F-No.	Drawing-No.																																																									
X.X	±0.20			26.05.2014	Ray		ASS 6448 CO																																																									
X.XX	±0.10			03.05.2016	Amy		A-MO 4/4-SF																																																									
X.XXX	±0.05																																																															
DIM	TOL																																																															
Angle	±2°																																																															
Angle																																																																
	1	2	3	4	5	6	7																																																									

Specifications:

Material: Poly Carbonate(PC) UL94V-2
Housing: High strength copper alloy
Contact blade: High strength copper alloy
100 micron Nickel underplated
Plating type: 8% Phosphor Bronze
Plating thickness: 6u" gold plated
Operating temperature: -40°C to +125°C

Electrical:

Current rating: 250V AC max. at 2A
Dielectric: 500V AC
Insulation resistance: 500MQ
Termination resistance: 35MQ max after environmental tests
Tensile strength: 20 LBS (89N) min.
Durability: 500 mating cycles

Complies with FCC68/F

RoHS compliant
Unit: mm

Scale	Free TOLERANCE	Free TOL	Id.	Date	Name	Customer-F-No.	Drawing-No.
X.X	±0.20			26.05.2014	Ray		ASS 6448 CO
X.XX	±0.10			03.05.2016	Amy		A-MO 4/4-SF
X.XXX	±0.05						
DIM	TOL						
Angle	±2°						
Angle							



ASS 6448 CO rev01

A-MO 4/4-SF

Replace Sheet