



PART DESCRIPTION	"A" THREAD	øB MIN	øC MAX	H REF	øJ		P REF REC	S REF	T REF	PANEL THK <sup>4</sup>	DRILL HOLE DIA. (REF.)
					MIN EXP	MAX REC					
CES-3-T1-AL-2.5	1 3/8-12 UNF	1.10 [27,94]	1.91 [48,52]	1.65 [41,9]	.60 [15,3]	.17 [4,57]	3.76 [95,5]	1.25 [31,2]	.31 [7,88]	1.5 [38]	1.38 [35,1]

NOTES:

- <sup>1</sup> NUT MATERIAL: ALUMINUM 6061-T6 WITH FINISH OF HARD ANODIZE PER MIL-A-8625F, TYPE III, CLASS 2, DYED BLACK AND NON-REFLECTIVE COATING.
- <sup>2</sup> BOOT: HEAT SHRINKABLE, MATERIAL IN ACCORDANCE WITH -3 POLYOLEFIN
- <sup>3</sup> PART TO BE MARKED AS SHOWN.
- <sup>4</sup> THIS PART IS DESIGNED TO FIT THROUGH A PANEL OR BULKHEAD WITH A WALL THICKNESS (REF.) AS INDICATED IN TABLE.
- <sup>5</sup> O-RING MATERIAL: NITRILE (BUNA-N)

If this document is printed it becomes uncontrolled. Check for the latest revision

CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES. METRIC DIMENSIONS ARE IN BRACKETS.	DRAWN UNGUYEN	APPROVED JKUSTER	 Tyco Electronics Raychem Molded Parts 305 Constitution Dr Menlo Park, CA 94025
	DECIMAL TOLERANCES .XXX ± 0.005 [0.13 mm] .XX ± 0.01 [0.25 mm] .X ± 0.1 [0.50 mm]		
ANGLE TOLERANCE .X ± 1 DEG.	THIRD ANGLE PROJECTION		TITLE <b>CABLE ENTRY SEAL,          3 ENTRY, ALUMINUM</b>
© 2009 Tyco Electronics Corporation. All rights reserved.	SIZE <b>B</b>	CODE IDENT. NO. <b>06090</b>	DWG. NO. <b>CES-3-T1-AL-2.5</b>