

## Fuse - FUSE 10,3X38 20A PV - 3061363

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse, 10.3x38 mm, up to 1000 V DC, gPV characteristics

The figure shows the 10 A version

### Product Features

- Use in PV lines with a nominal voltage of up to 1000 V DC

### Key commercial data

|                        |   |
|------------------------|---|
| Packing unit           | 1 PCE   |
| Minimum order quantity | 10 PCE  |
| GTIN                   | <br>4 046356 523790 |
| Custom tariff number   | 85361050  |
| Country of origin      | SLOVENIA  |

### Technical data

#### General

|   |                    |
|---|--------------------|
| Color                                   | black              |
| Inflammability class according to UL 94 | V0                 |
| Fuse                                    | Midget / 10.3 x 38 |
| Connection in acc. with standard        | IEC 60269-6        |
| Nominal current $I_N$                   | 20 A               |

#### Dimensions

|        |       |
|--------|-------|
| Width  | 10 mm |
| Length | 38 mm |

# Fuse - FUSE 10,3X38 20A PV - 3061363

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000035 |
| ETIM 4.0 | EC002704 |
| ETIM 5.0 | EC002704 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 11     | 39121514 |
| UNSPSC 12.01  | 39121514 |
| UNSPSC 13.2   | 39121514 |
| UNSPSC 6.01   | 30211915 |
| UNSPSC 7.0901 | 39121514 |

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27142001 |
| eCl@ss 4.1 | 27142001 |
| eCl@ss 5.0 | 27142001 |
| eCl@ss 5.1 | 27142002 |
| eCl@ss 6.0 | 27142002 |
| eCl@ss 7.0 | 27142002 |
| eCl@ss 8.0 | 27142002 |

## Approvals

### Approvals

---

Approvals

UL Recognized

---

Ex Approvals

---

Approvals submitted

---

### Approval details

|   |
|---|
| UL Recognized  |
|---|

