



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	SEE ECN 80-0823-2	FN 8/12/80	RG 8/12/80
01 ₂	ECN 92-0010	AD 9/23/92	BB 10/1/92

ELECTRICAL
Nominal Impedance (Ohms) <u>50</u>
Frequency Range (GHz) DC to <u>18</u>
Volt Rating (VRMS MAX) @ Sea Level <u>190</u>
VSWR <u>1.05 ± .005 f</u> (GHz)
Insertion Loss (dB MAX) <u>.03 f</u> (GHz)
RF Leakage (dB MIN) <u>-[60 - f(GHz)]</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u>
Contact Resistance (Milliohms MAX) Center Contact <u>2.0</u> Outer Contact <u>2.0</u> Cable to Housing <u>N/A</u>
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>
I.R.(Megohms MIN) <u>10,000</u>

MECHANICAL
Interface Dimensions MIL-STD-348A, Fig. <u>310.2</u>
Recommended Mating Torque <u>N/A</u>
Mating Characteristics: Insertion (MAX Lbs) <u>3.0</u> Withdrawal (MIN Oz) <u>1.0</u>
Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u>
Center Contact Captivation Axial (Lbs) <u>6.0</u> Radial (In-Oz) <u>4.0</u>
Cable Retention Axial Force (Lbs) <u>N/A</u> Torque (In-Oz) <u>N/A</u>
Weight (Grams) <u>N/A</u>

ENVIRONMENTAL
Temperature Rating <u>-55°C to +105°C</u>
Vibration MIL-STD-202, Method <u>204, Condition D.</u>
Shock MIL-STD-202, Method <u>213,</u> <u>Condition I.</u>
Thermal Shock MIL-STD-202, <u>Method 107, Condition A</u>
Moisture Resistance MIL-STD-202, <u>Method 106</u>
Corrosion - MIL-STD-202, Method <u>101, Condition B, 5% salt spray</u>

HOUSING
DIELECTRIC
CENTER CONTACT
COMPONENT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

MATERIAL
STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303
TFE FLUOROCARBON PER ASTM-D-1457
BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H
DATE DRAWN BY TIM CHECKED BY RMF APPD BY GH
DATE <u>3/2/79</u> DATE <u>3/2/79</u>
USE ASS'Y PROCEDURE
NO. AP. <u>N/A</u>

FINISH
PASSIVATE PER ASTM-A380
N/A
GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
TITLE OSM FLANGE MOUNT JACK RECEPTACLE TAB TERMINAL
SIZE B
CODE IDENT NO. 26805
2052-1133-02
REV 01 ₂
SCALE 10 : 1
SHEET 1 OF 1