

**General ordering data**

Order No.	1028380000
Part designation	WFF 35 BL
Version	Stud terminal, 35 mm <sup>2</sup> , Threaded stud connection, Wemid, blue, TS 35
EAN	4008190143428
Qty.	10 pc(s).

**Product notes**

Note, accessories	WAH 35 in blue, order no. 1064480000
-------------------	--------------------------------------

**PT OKIECEX/ATEX rating data**

EU-type examination certificate	KEMA98ATEX1684U
Download, German	KEMA98ATEX1684U_d.pdf
Download English	KEMA98ATEX1684U_e.pdf
ATEX voltage	1100 V
ATEX current	109 A
ATEX conductor cross-section	35 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

**Additional technical data**

Colour of insulating material	blue
Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	closed
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Stud terminal

**CSA rating data**

Voltage (CSA)	600 V
CSA current	130 A
Min. cross-section (CSA)	AWG 14
Max. cross-section (CSA)	AWG 2

**Conductors for clamping (rated connection)**

Type of connection	Threaded stud connection
--------------------	--------------------------

**Conductors for clamping (rated connection)**

Connection direction	on side
Flexible, min.	2.5 mm <sup>2</sup>
Flexible, max.	50 mm <sup>2</sup>

**Dimensions**

Width	27 mm
Height of lowest version	54.5 mm
Length	107 mm
Weight	94.9 g
TS 35 offset	53.5 mm

**Rating data**

Rated cross-section	35 mm <sup>2</sup>
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	125 A
Current with max. conductor	150 A
Pollution severity	3

**Strap connection**

Gauge to EN 50043	C4
Strap 1, max.	6 x 13 x 0.5
Strap 1, min.	3 x 13 x 0.5
Strap 2, min.	2 x 15,5 x 0,8

**Stud connection**


2 cable lugs to DIN 46234	2.5...35 mm <sup>2</sup>
2 cable lugs to DIN 46234	6...25 mm <sup>2</sup>
Cable lug to DIN 46234	2.5...50 mm <sup>2</sup>
Cable lug to DIN 46234	6...25 mm <sup>2</sup>
Clamping range, max.	50 mm <sup>2</sup>
Clamping range, min.	2.5 mm <sup>2</sup>
Stud size for spade connection	M 6
Tightening torque range	3.0...6.0 Nm

**UL rating data**

Voltage (UL)	1,000 V
Current (UL)	115 A
Min. cross-section (UL)	AWG 14
Max. cross-section (UL)	AWG 2

**Approvals**

Approvals institutes



## Approvals



## Classifications

ETIM 2.0	NK
ETIM 3.0	EC002020
eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

## Similar products

Order No.	Part designation	Version
1028300000	WFF 35	Stud terminal, 35 mm <sup>2</sup> , Threaded stud connection, Wemid, dark beige, TS 35
1028400000	WFF 70	Stud terminal, 70 mm <sup>2</sup> , Threaded stud connection, Wemid, dark beige, TS 35
1028480000	WFF 70 BL	Stud terminal, 70 mm <sup>2</sup> , Threaded stud connection, Wemid, blue/light blue, TS 35
1028500000	WFF 120	Stud terminal, 120 mm <sup>2</sup> , Threaded stud connection, Wemid, dark beige, TS 35
1028580000	WFF 120 BL	Stud terminal, 120 mm <sup>2</sup> , Threaded stud connection, Wemid, blue, TS 35
1857540000	WFF 120/M12/AH	Stud terminal, 120 mm <sup>2</sup> , Wemid, TS 35
1028600000	WFF 185	Stud terminal, 185 mm <sup>2</sup> , Threaded stud connection, Wemid, dark beige, TS 35
1028680000	WFF 185 BL	Stud terminal, 185 mm <sup>2</sup> , Threaded stud connection, Wemid, blue, TS 35
1028700000	WFF 300	Stud terminal, 300 mm <sup>2</sup> , Threaded stud connection, Wemid, dark beige, TS 35
1028780000	WFF 300 BL	Stud terminal, 300 mm <sup>2</sup> , Threaded stud connection, Wemid, blue, TS 35