


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPST
CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X±0.4, X.XX±0.25
 3. TERM. NOS. FOR REF ONLY
 4. RATING: 50 MILLI-AMPS, @12VDC
 5. TRAVEL: 0.25 +0.2/-0.1mm
 6. CONTACT RESISTANCE: 100 MOHMS MAX
 7. OPERATING FORCE: 350 ±100 GF
 8. PACKAGING: TAPE AND REEL 1500 PER
 9. ACTUATOR COLOR: BLACK
 10. ▲ DENOTES CRITICAL PARAMETER.
 11. 2002/95/EC (ROHS) COMPLIANT
 12. OPERATING TEMPERATURE: -20°C TO 70°C
 13. CONTACT MATERIAL: SILVER
 14. MECHANICAL/ELECTRICAL LIFE: 100,000 CYCLES

C	21086	7.0 MAX WAS 5.8 MAX	3/27/13	EBP
B	21024	ROHS, LIFE, TEMP, PLATE, MOHM	2/12/13	EBP
A	14175	RELEASED FOR PRODUCTION	7/19/04	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
E-SWITCH		4:1	7/19/04	AR	P010615	C
TL 3304AF3500G						

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED