

Specification Sheet

Part Number: T30R7C2



Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Purple, 100/pkg

| | |
|---------------------|--|
| Article Number | 116-03017 |
| Type | T30R |
| Color | Purple (PE) |
| Features & Benefits | <ul style="list-style-type: none">• Inside serrations allow for strong hold on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Purple, 100/pkg

Global Part Name

T30R-PA66-VT

Minimum Tensile Strength (Imperial)

30.0

Minimum Tensile Strength (Metric)

135.0

Length L (Imperial)

5.8

Length L (Metric)

148.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.14

Width W (Metric)

3.6

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.38

Bundle Diameter Max (Metric)

35.0

| | |
|-----------------------------|-----|
| Thickness T (Metric) | 1.1 |
|-----------------------------|-----|

| | |
|-----------------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

| | |
|--------------------------|------|
| Material Shortcut | PA66 |
|--------------------------|------|

| | |
|--------------------|-------------|
| US MIL SPEC | SAE-AS33671 |
|--------------------|-------------|

MS3367-5-7
Flammability

| | |
|----------|---------------------|
| UL 94 V2 | Halogen free |
|----------|---------------------|

| | |
|-----|---------------------------------------|
| Yes | Operating Temperature (Metric) |
|-----|---------------------------------------|

| | |
|----------------------------------|-----------------------|
| -40°F to +185°F (-40°C to +85°C) | ROHS Complaint |
|----------------------------------|-----------------------|

| | |
|-----|--|
| Yes | Certification/Specification WEB |
|-----|--|

| | |
|--------------------------------|---------------------------|
| UL-ZODZ.E64139 CAGE Code 53421 | UL Recognized (US) |
|--------------------------------|---------------------------|

| | |
|-----|----------------------------------|
| Yes | UL Listed (US and Canada) |
|-----|----------------------------------|

| | |
|-----|--------------------------------------|
| Yes | UL Recognized (US and Canada) |
|-----|--------------------------------------|

| | |
|-----|--|
| Yes | |
|-----|--|

| | |
|-----------------------------------|-----|
| Package Quantity(Imperial) | 100 |
|-----------------------------------|-----|

| | |
|----------------------------------|-----|
| Package Quantity (Metric) | 100 |
|----------------------------------|-----|

Customs Number

3926909987

Weight (Metric)

0.7