

Specification Sheet

Part Number: D10H4



Screw Mount Cable Clip, 0.39" Max Bundle Dia, 0.31" Mounting Hole Dia, POM, Black, 500/pkg

| | |
|--------------------------------|---|
| Article Number | 211-70200 |
| Type | 8D10 |
| Color | Black (BK) |
| Features & Benefits | Available in three sizes, HellermannTyton screw mount clips offer quick, snap-in action. These clips allow for easy release for wiring changes or replacements, saving both time and money. |
| Quantity Per | bag |
| Product Description | Developed for fixing pipes, cables and hoses, the D-Clips elastic locking system ensures optimal fixing and at the same time, easy removal of the fixed elements by simply pressing the lower latch down and pulling the fixed element. |
| Short Description | Screw Mount Cable Clip, 0.39" Max Bundle Dia, 0.31" Mounting Hole Dia, POM, Black, 500/pkg |

Global Part Name

8D10-POM-BK

Length L (Imperial)

0.67

Length L (Metric)

17.0

Fixation Method

screw-hole

Variant

Closed

Width W (Imperial)

0.59

Width W (Metric)

15.0

Bundle Diameter Min (Imperial)

0.39

Bundle Diameter Min (Metric)

10.0

Bundle Diameter Max (Imperial)

0.39

Bundle Diameter Max (Metric)

10.0

Nominal Diameter (Imperial)

3/8

Nominal Diameter (Metric)

10.0

Wall Thickness WT (Imperial)

0.08

Wall Thickness WT (Metric)

2.0

Mounting Hole Diameter D (Imperial)

0.31

Mounting Hole Diameter D (Metric)

8.0 mm

| | |
|--|------|
| Mounting Hole Diameter D Min (Imperial) | 0.31 |
|--|------|

| | |
|--|------|
| Mounting Hole Diameter D Max (Imperial) | 0.31 |
|--|------|

| | |
|--|-----|
| Mounting Hole Diameter D Max (Metric) | 8.0 |
|--|-----|

| | |
|-----------------|------------------|
| Material | Polyacetal (POM) |
|-----------------|------------------|

| | |
|--------------------------|-----|
| Material Shortcut | POM |
|--------------------------|-----|

| | |
|---------------------|----------|
| Flammability | UL 94 HB |
|---------------------|----------|

| | |
|------------------------------|----|
| UV Resistant (Yes/No) | No |
|------------------------------|----|

| | |
|---------------------------------------|----------------------------------|
| Operating Temperature (Metric) | -40°F to +194°F (-40°C to +90°C) |
|---------------------------------------|----------------------------------|

| | |
|------------------------------------|-----|
| Reach Complaint(Article 33) | Yes |
|------------------------------------|-----|

| | |
|-----------------------|-----|
| ROHS Complaint | Yes |
|-----------------------|-----|

| | |
|-----------------------------------|-----|
| Package Quantity(Imperial) | 500 |
|-----------------------------------|-----|

| | |
|----------------------------------|-----|
| Package Quantity (Metric) | 500 |
|----------------------------------|-----|

| | |
|-----------------------|------------|
| Customs Number | 3926909987 |
|-----------------------|------------|

| | |
|-----------------------------|------|
| Content Unit(BMEcat) | pcs. |
|-----------------------------|------|

| | |
|------------------------|-----|
| Weight (Metric) | 2.5 |
|------------------------|-----|

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)