



Specifications

- Ideal for use where corrugated and/or paper products cannot be used
- Durable 1/4" (6mm) thick dissipative, crosslink polyethylene foam laminated to conductive fluted Plastek
- Galvanized Steel Turntable located at the bottom
- Size: Choice of 12-1/2" (318mm) or 15-1/2" (395mm) circle
- Very low profile - 1" high
- Weight capacity 50 lbs (23Kg), ideal for working on heavier assemblies
- Volume Resistance 1 x 10⁶ to < 1 x 10⁹ ohms per ANSI/ESD STM11.12
- Meets worksurface required limit of ANSI/ESD S20.20 per ANSI/ESD S4.1 and ESD TR53
- Electrostatic charges removed to ground via contact on grounded ESD worksurface or via our [47204](#) ground cord
- Made in the United States of America



47203 in use

([47204](#) Ground cord sold separately)



Galvanized Steel Turntable

Item	Size (Diameter)
47202	12-1/2" (318mm)
47203	15-1/2" (394mm)



Made in the United States of America

Specifications and procedures are subject to change without notice

Unless specified tolerances are +/- 10%

ESD PLASTEK TURNTABLE

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
47202

DATE:
March
2016