



DESIGNED FOR USE WITH .141 DIA S/R CABLE	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.142
CONTACT	.0404

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₀	REVISED	2/16/97	ICpm 2/16/97

COMPONENT	MATERIAL	FINISH
HOUSING	BRASS PER QQ-B-626 COMP. 360	GOLD PLATE PER MIL-G-45204
HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
"O" - RING	SILICONE RUBBER PER ZZ-R-765, CLASS 2B	N/A

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 304.1	Temperature Rating <u>-65°C to +105°C</u>
Frequency Range (GHz) DC to <u>11</u>	Recommended Mating	Vibration MIL-STD-1344, Method 2005, Condition IV, 30g Peak
Volt Rating (VRMS MAX)	Torque <u>12-15 In Lbs</u>	Shock MIL-STD-1344, Method 2004, Condition G
@ Sea Level <u>600</u>	Mating Characteristics:	Thermal Shock MIL-STD-1344, Method 1003, Test Condition A, Except High Temp 115°C
VSWR <u>1.07 + .007(f)GHz</u>	Insertion (MAX Lbs) <u>2.0</u>	Corrosion - MIL-STD-1344, Method 1001, Condition B
Insertion Loss (dB MAX) <u>.03√(f)GHz</u>	Withdrawal (MIN Oz) <u>2.0</u>	
RF Leakage (dB MIN) <u>-90dB</u>	Force to Engage and	
Between 2 to 3 GHz	Disengage (In/Lbs MAX) <u>6.0</u>	
Corona, 70,000 Ft (VRMS MIN) <u>375</u>	Center Contact Captivation	
Dielectric Withstanding Voltage	Axial (Lbs) <u>6.0</u>	
(VRMS MIN) @ Sea Level <u>1500</u>	Radial (In/Oz) <u>N/A</u>	
Contact Resistance (Milliohms MAX)	Cable Retention	
Center Contact <u>1.5</u>	Axial Force (Lbs) <u>60 Lbs Min</u>	
Outer Contact <u>2.0</u>	Torque (In/Oz) <u>55 In Oz Min</u>	
RF High Potential @ Sea Level	Weight (Grams) <u>TBD</u>	
(VRMS MIN @ 5 MHz) <u>1000</u>		
I.R.(Megohms MIN) <u>5000</u>		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	DRAWN BY <i>B.M. EDWARDS</i> DATE <i>2/5/91</i>		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
	CHECKED BY <i>K.C. MAHER</i> 2/7/91		TITLE OSN BULKHEAD FEEDTHROUGH CABLE JACK-DIRECT SOLDER ATTACHMENT	
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.	APPD BY <i>NGB</i> 2/7/91	USE ASS'Y PROCEDURE	SIZE B	CODE IDENT NO. 26805
	408-04911 NO. AP. (30-005)	NO. AP. (30-005)	SCALE 2:1	3004-7941-00
			REV 02 ₀	SHEET 1 OF 1