



REV	ECN NO	REVISIONS	DRN	CKD	APP	DATE
A		NEW RELEASE	TWC			




NOTES:

- EPOXY COLOR: WATER CLEAR.
- DIE: GaAsP/GaP GREEN LED.
- LEADS: TIN (Sn) OVER NICKEL (Ni)
- SOLDER ADHERANCE: BOTH LEADS PER MIL-STD-202E, METHOD 208C.
- SUFFIX -202F FOR 20-PCS ON A SAMPLE TAPE STRIP.
- SUFFIX -207F FOR 180 mm DIA. REEL, 8 mm WIDE TAPE, PACKAGED 2000 PCS PER REEL WITH A PITCH OF 4 mm.
- DEVICES POSITIONED ON REEL WITH CATHODE SIDE TOWARDS SPROCKET.
- DIALIGHT P/N: 597-3301-202F, 597-3301-207F.
- TAPE AND REEL LEDS MAY REQUIRE RE-TAPING AFTER TWELVE MONTHS.
- DEVICES HAVE A MOISTURE SENSITIVITY LEVEL OF "2" CAUTION LABEL APPLIED AS PER JEDEC STD. 033.
- THIS PRODUCT IS RoHS COMPLIANT (Pb FREE). EACH BAG AND REEL IS MARKED WITH RoHS COMPLIANT LABEL 9100-117-0852-99 OR EQUIVALENT MARKING.

OPERATING CHARACTERISTICS AT 25°C AMBIENT					
CHARACTERISTICS	MIN	TYP	MAX	UNITS	TEST CONDITIONS
LUMINOUS INTENSITY	11.2	19.6	28.0	mc d	$I_f = 10 \text{ mA}$
FORWARD VOLTAGE		2.0	2.5	V	$I_f = 10 \text{ mA}$
REVERSE CURRENT		.01	10.0	μA	$V_R = 12 \text{ V}$
PEAK WAVELENGTH		572		nm	$I_f = 10 \text{ mA}$
DOMINANT WAVELENGTH	564	570	576	nm	$I_f = 10 \text{ mA}$
VIEWING ANGLE (2 θ 1/2)		120		DEG.	

ABSOLUTE MAXIMUM RATING AT 25°C AMBIENT		UNITS
POWER CONSUMPTION	95	mW
REVERSE VOLTAGE	12	V
DERATE LINEARLY FROM 60 °C	.75	$\text{mA}/^\circ\text{C}$
CONTINUOUS FORWARD CURRENT	30	mA
SOLDERING TEMPERATURE FOR 10 SEC.	260	$^\circ\text{C}$
OPERATING TEMPERATURE	-40 TO 100	$^\circ\text{C}$
STORAGE TEMPERATURE	-40 TO 100	$^\circ\text{C}$



THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE: DRAWING SCALE ALL DIM'S IN: INCHES (MM)	DRAWING NUMBER C-17258	REV A
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE GREEN PLCC-2 SMT LED, RoHS COMPLIANT	
FRACTIONS: $\pm 1/64$ DECIMALS (.XX): $\pm .01$ DECIMALS (.XXX): $\pm .005$ DECIMALS (.XXXX): $\pm .0005$ ANGLES: $\pm 1^\circ$	MATERIAL	
FINISH:	Dialight 1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727	
FSCM 83330	SHEET 1 OF 1 FAMILY TABLE:	