

Uninterruptible power supply - STEP-UPS/12DC/12DC/4 - 2868693

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Uninterruptible power supply with integrated battery module. The STEP-BAT/LIPO/18.5 DC/1.4 AH battery module can be re-ordered separately.

Product Features

- UPS with integrated LiPo-based power storage



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	600.0 g
Custom tariff number	85371091
Country of origin	Germany

Technical data

Dimensions

Width	108 mm
Height	90 mm
Depth	61 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	-20 °C ... 45 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, non-condensing)
Noise immunity	EN 61000-6-2

Input data

Nominal input voltage range	12 V DC
Input voltage range	10 V DC ... 16.5 V DC

Uninterruptible power supply - STEP-UPS/12DC/12DC/4 - 2868693

Technical data

Input data

Current consumption (charging process)	< 0.8 A (Charging (I _{Charge} = max, I _{Out} = 0))
Current consumption (maximum)	6 A
Current consumption (idle)	< 30 mA
Buffer period	100 min (1 A)
	50 min (2 A)
	30 min (3 A)
	23 min (4 A)
Input fuse	7 A (slow-blow, internal)
Maximum current I _{max}	6 A

Output data (12 V DC mains operation)

Nominal output voltage	12 V DC
Nominal output current	4 A (0°C ... 40°C)

Output data (12 V DC battery operation)

Nominal output voltage	12 V DC
Output voltage range (depends on the input voltage)	10 V DC ... 15 V DC (U _{Out} = U _{In (t-1)})
Nominal output current	4 A (0°C ... 40°C)

General output data

Efficiency	> 97.4 % (Mains operation, with charged power storage)
------------	--

General

IQ technology	No
Net weight	0.46 kg
Memory medium	Lithium polymer
Protection class	III
MTBF (IEC 61709, SN 29500)	> 1997000 h (40°C)
Mounting position	horizontal DIN rail NS 35, EN 60715
Assembly instructions	Can be aligned: Horizontally 0 mm, vertically 50 mm
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL Listed UL 508
	UL/C-UL Recognized UL 60950

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²

Uninterruptible power supply - STEP-UPS/12DC/12DC/4 - 2868693

Technical data

Connection data, input

Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	6.5 mm
Screw thread	M3

Connection data, output

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	6.5 mm
Screw thread	M3

Connection data for signaling

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	6.5 mm
Screw thread	M3

Charging process

Quality check of battery	Yes, every time it is charged and cyclically once a month
Deep discharge protection	< 15 V DC

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Shock	30g in each direction, according to IEC 60068-2-27
Noise immunity	EN 61000-6-2
Connection in acc. with standard	CUL
Standards/regulations	EN 61000-4-3

Uninterruptible power supply - STEP-UPS/12DC/12DC/4 - 2868693

Technical data

Standards and Regulations

	EN 61000-4-4
	EN 61000-4-6
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL Listed UL 508
	UL/C-UL Recognized UL 60950
Vibration (operation)	< 15 Hz, amplitude ±2.5 mm (according to IEC 60068-2-6)

Classifications

eCl@ss

eCl@ss 4.0	27040603
eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27040603
eCl@ss 8.0	27049201

ETIM

ETIM 4.0	EC000382
ETIM 5.0	EC000382

UNSPSC

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

Approvals

Approvals

Approvals

UL Recognized / UL Listed / cUL Recognized / cUL Listed / IECCEB Scheme / EAC / EAC / cULus Recognized / cULus Listed

Uninterruptible power supply - STEP-UPS/12DC/12DC/4 - 2868693

Approvals

Ex Approvals

Approvals submitted

Approval details

UL Recognized

UL Listed

cUL Recognized

cUL Listed

IECEE CB Scheme

EAC

EAC

cULus Recognized

cULus Listed

Uninterruptible power supply - STEP-UPS/12DC/12DC/4 - 2868693

Drawings

Block diagram

