



NOTE:

1. UL2725 USB 2.0 REV CABLE.(28AWG\*1PAIR+24AWG\*2C),AL-FOIL AND BRAID SHIELDED (A-MALLOY) WITH A DRAIN WIRE(BARE COPPER),PVC JACKET BLACK OD:4.5±0.15mm.2. CONNECTOR: P1:USB A TYPE FMALE, SOLDED TYPE,WHITE PBT INSULATIPON, GOLD PLATED CONTACTS,NICKEL PLATED SHELL. P2:USB A TYPE MALE, SOLDED TYPE,WHITE PBT INSULATIPON, GOLD PLATED CONTACTS,NICKEL PLATED SHELL.
3. HOOD:P1:07PS/PM MOUDLE: BLACK PC+ABS.
4. TEST: 100% ELECTRICAL TESTING.
5. PCKing: USB 2.0 adapter Cable+07PM adapter+2PCS 4-40 SCREWS



REV	DESCRIPTION OF CHANGE	DATE
B	CHANGE SIZE	03/30/16
A	INITIAL RELEASE	02/23/16
REV	DESCRIPTION OF CHANGE	DATE

TOLERANCE	INCHES	M/M	TRIPP-LITE			
.X	.015	.30	SCALE	NONE	REV	B
.XX	.010	.10	UNIT	MM		
.XXX	.005	.05	SHEET	1/1	DWG NO.	
DRAWN BY CAI			DATE	03/30/16		
CHECK BY			TITLE USB 2.0 M/F MODULE			
APPD BY			PART NO. U024-001-KPA-BK			