



CT-3001/CCP • CT-3001/CCPINT • CT-3001/CCPUK
 • CT-3001/CCPAUS • CT-3001/CCPTO
 MULTI-USE (CRIMP • CUT • PUNCH) TOOL

This tool meets requirements of Safety for Hand Held, Motor-Operated Electric Tools specification UL 60745-1 and CSA C22.2 No 60745-1. Tool is listed under CSA file number 268531.

NOTES, UNLESS OTHERWISE SPECIFIED:

The CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK, CT-3001/CCPAUS and CT-3001/CCPTO Battery Operated Multi-Use Tools are designed to crimp and cut:

- Crimps Panduit Copper and Aluminum compression connectors using Panduit Crimping Dies. Go to www.panduit.com for more information.
- Cuts Aluminum and Copper code conductor cable up to 1" [25mm].
- Cuts Aluminum and Mild Steel Threaded Rod; M5 to M12, and 1/4 to 1/2 UNC Thread.
- Punch Capacity of 2" (50 mm) conduit size in 10 Gauge (3.41 mm) mild steel with standard Greenlee punches and Panduit Punch Drive Adapter.

The CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK and CT-3001/CCPAUS Tools include:

| Qty. | Description / Item | | | | | | | | |
|--------------------------------|---|---------------------|----------------------------|--|--|--------------------------------|--------------------------------|---------------------|----------------------------|
| 1 | Battery Operated Hydraulic Multi-Use (Crimp, Cut) Tool | | | | | | | | |
| 2 | Rechargeable Battery (Makita Lithium-Ion 18VDC, 3Ah) | | | | | | | | |
| 1 | <table border="0" style="width: 100%; text-align: center;"> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Plug Type A (North America)</td> <td>Plug Type C (International)</td> <td>Plug Type G (UK)</td> <td>Plug Type I (Australia)</td> </tr> </table> Makita Battery Charger – Regional (reference images above for regional plug type) | | | | | Plug Type A (North America) | Plug Type C (International) | Plug Type G (UK) | Plug Type I (Australia) |
| | | | | | | | | | |
| Plug Type A (North America) | Plug Type C (International) | Plug Type G (UK) | Plug Type I (Australia) | | | | | | |
| 1 | Tool Case | | | | | | | | |
| 1 | Set of "UAW" Die Adapters | | | | | | | | |

The CT-3001/CCPTO Tool includes:

| Qty. | Description / Item |
|------|---|
| 1 | Battery Operated Hydraulic Multi-use (Crimp, Cut, Punch) Tool |
| 1 | Set of "UAW" Die Adapters |

Technical Information:

| | |
|---------------------------------|--|
| Tool Weight (including battery) | 7.1 lbs. (3.2 kg) |
| Dimensions (including battery) | 17.5" L x 4.6" H x 3.0" W [444 L x 116 H x 75 W] mm |
| Crimping Force | 6.7 tons (60 kN) |

Tools are to be used with Panduit crimp dies, cable cutters, threaded rod cutters, and punch drive adapters are sold separately. Go to www.panduit.com for more information.

"UAM" adapter for cable cutting applications is sold separately.

A copy of operation manual and accessory information can be found at: www.panduit.com.

Dimensions in [brackets] are in millimeters. All dimensions are for reference only.

| REV | DATE | BY | CHK | APR | DESCRIPTION | ECN | CT-3001/CCP, CT-3001/CCPINT, CT-3001/CCPUK, CT-3001/CCPAUS and CT-3001/CCPTO | | | | CUSTOMER DRAWING | |
|-----|---------|-----|-----|------|------------------|--------|---|------------------|------------|---------------|--------------------------------|-----------|
| 00 | 7-25-16 | BKA | ACC | JADE | DRAWING RELEASED | 010819 | ITEM REVISION NAME: 00084SLG_DC/00 | | | | PANDUIT | |
| | | | | | | | UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± --- (.xxx) ± --- (.xx) ± --- ANGLES ± --- | | | | MATERIAL: ----- | |
| | | | | | | | THIRD ANGLE PROJECTION | | | | DRAWING NUMBER: 00084SLG_DC | |
| | | | | | | | DRAWN BY: BKA | DATE: 7-21-16 | CHK ACC | SCALE NONE | SHT 1 OF 1 | SIZE B |