

## USB 3.1 Gen 1 (5 Gbps) Adapter, USB Type-C (USB-C) to USB Type-A M/F

MODEL NUMBER: U428-000-F



Connects an existing USB Type-A device or cable to the USB-C port on your smartphone, tablet, Ultrabook or computer in order to share data or charge a mobile device.

### Description

The U428-000-F USB 3.1 Gen 1 Adapter connects your new USB-C smartphones, tablets, Ultrabooks and computers to your existing USB-A devices or cables in order to share data or charge a mobile device. It supports USB 3.1 Gen 1 data transfer speeds up to 5 Gbps and power output up to 3A for fast charging of mobile devices. Unlike traditional USB connectors that can be attached only one way, the reversible USB-C male connector plugs into a USB port in either direction for fast, fumble-free connection every time. Nickel-plated molded end connectors and gold-plated copper contacts ensure superior conductivity and long life. Slim form supports evolving design trends toward smaller devices. Backward compatible with USB 2.0 devices.

*USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum*

### Features

#### Supports USB 3.1 Gen 1

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Supports power output up to 3A—perfect for fast charging most mobile devices
- Uses same USB-A female connector as USB 3.0 devices
- Backward compatible with USB 2.0 devices

#### Reversible USB-C Male Connector

- Fumble-free reversible plug ensures fast, easy connection every time
- Strong enough for tablets, laptops and other larger platforms

#### Premium Construction

### Highlights

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Supports power output up to 3A for fast charging of mobile devices
- Fumble-free reversible USB-C plug on one end
- Backward compatible with USB 2.0 devices
- Slim design tailored for emerging trends toward smaller devices

### System Requirements

- Device with USB-C port
- Device or cable with USB-A plug

### Package Includes

- U428-000-F USB 3.1 Gen 1 (5 Gbps) Adapter, USB-C to USB-A M/F



- Gold-plated copper contacts and nickel-plated molded ends provide a lifetime of heavy use and superior conductivity
- Slim, sleek design tailored for emerging design trends toward smaller devices

## Specifications

OVERVIEW	
UPC Code	037332190826
Technology	USB (all versions); USB 3.1 (Gen 1)
INPUT	
Bus Powered	Yes
PHYSICAL	
Shipping Dimensions (hwd / in.)	3.900 x 5.900 x 0.500
Shipping Weight (lbs.)	0.0220
Unit Packaging Type	Polybag
Unit Dimensions (hwd / in.)	0.4 x 0.7 x 0.8
Unit Weight (lbs.)	0.01
Unit Weight (kg)	0.00
Material of Construction	PVC
Color	Black
ENVIRONMENTAL	
Operating Temperature Range	32 to 158 F (0 to 70 C)
Storage Temperature Range	14 to 176 F (-10 to 80 C)
Relative Humidity	10% to 90 % RH, Non-Condensing
BTUs	0.34 BTU/Hr
Power Consumption (Watts)	0.1
Power Provided to Connected Device(s)	5V 3A (15W) Output
CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	USB 3.0 A (FEMALE)
Connector Plating	Nickel



<b>FEATURES &amp; SPECIFICATIONS</b>	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
UASP Support	Yes
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>